

# BT-390

## WINDSCREEN SEALANT



ISO 9001

### 1. Product & Company Identification

#### Product Details

**Product name:** BT-390 Windscreen Sealant  
**Physical form:** Extruded solid putty tape  
**Odour:** Odourless  
**CAS No.:** Mixture  
**Flammability:** Very low

#### Company Details

**Manufacturer:** Mohm Chemical Sdn Bhd  
**Address:** No. 32, Jalan Temenggong, Off Jalan Tampoi,  
81100 Johor Bahru, Johor, Malaysia.  
**Tel:** + 60-7-3331222  
**Fax:** + 60-7-3320545/ + 60-7-3337919

### 2. Hazards Identification

#### Hazard Pictogram

None.

#### Classification

None.

#### Hazard Statement

None.

This Product is not classified as hazardous under current regulations.

### 3. Composition / Hazardous Components

| <u>Chemical Name</u> | <u>Hazardous</u>    |
|----------------------|---------------------|
| Synthetic Rubber     | Non currently known |

### 4. First-aid Measures

|                                 |   |
|---------------------------------|---|
| <b>In case of swallowed</b>     | <b>If large amount is swallowed, get medical attention</b>  |
| <b>In case of inhalation</b>    | <b>If adverse effects occur, remove to uncontaminated area. Get good medical attention.</b>                                     |
| <b>In case of skin contact:</b> | <b>Wash exposed skin with hand cleaner / soap &amp; water. Cool with water for at least 15 minutes if hot material is used.</b> |
| <b>In case of eyes contact:</b> | <b>Flush eyes with plenty of clean running tap water for at least 15 minutes</b>  |
| <b>Advice to doctor:</b>        | <b>Treat symptomatically.</b>   |



# BT-390

## WINDSCREEN SEALANT



ISO 9001

### 5. Fire Fighting Measures

|                               |   |
|-------------------------------|---|
| Flammability:                 | Very Low  |
| Suitable extinguishing media: | Dry Chemical, Foam, CO <sup>2</sup> , Water Fog |
| Flash Point                   | Minimum 180 °C                                  |

### 6. Accidental release measures

|          |   |
|----------|---|
| Methods: | Exclude sources of ignition and ventilation the area<br>Exclude non-essential personnel. Avoid breathing vapour |
|----------|---|

### 7. Handling and Storage

|                                    |  |
|------------------------------------|--|
| Handling:                          | Ensure good ventilation during processing. Wear safety shoes.  |
| Protection against fire/explosion: | General rules of fire prevention should be observed.           |
| Storage:                           | Keep in a cool shaded place, away from heat & direct sunlight. |

### 8. Exposure control / Personal protection

|                  |                             |
|------------------|-----------------------------|
| Hand protection: | Suitable protective gloves. |
| Eye protection:  | Safety / Protective Goggles |

### 9. Physical and Chemical Properties

|                         |                           |
|-------------------------|---------------------------|
| Form:                   | Extruded solid putty tape |
| Specify gravity:        | 1.4 ± 0.1                 |
| Colour:                 | Black                     |
| Odour:                  | Odourless                 |
| Melting Temperature     | Not Applicable            |
| Boiling point:          | Not Applicable            |
| Flash point:            | Minimum 180 °C            |
| Freezing Point          | Not Applicable            |
| Ignition Temperature:   | Non known                 |
| Vapour Pressure (25°C)  | Non known                 |
| Soluble in Water (25°C) | Negligible, below 1%      |

Note: the above information is not intended for use in preparing specification.

### 10. Stability and Reactivity

|                                   |  |
|-----------------------------------|--|
| Hazardous Decomposition Products: | Incomplete burning can produce CO, CO <sub>2</sub> , and other harmful products. |
| Hazardous Reaction:               | No dangerous reaction known  |

### 11. Toxicological Information

|              |                         |
|--------------|-------------------------|
| On the skin: | May cause sensitization |
| On the eye:  | Possibility irritating  |



# BT-390

## WINDSCREEN SEALANT



ISO 9001

### 12. Ecological Information

Large quantities of products should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface water.

### 13. Disposal considerations

Do not allow large quantities to enter the drains or watercourses or dispose of where ground surface may be affected. Residue in emptied containers should be covered and should be disposed of in accordance with regulations made under the control of Pollution & Environment Protection Acts.

### 14. Transport Information

Not Available

### 15. Regulatory Information

Not Available.

### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\*\* End Of SDS \*\*\*

