

# SAFETY DATA SHEET

REV: 03 DATE: 13 APRIL 2015

# x'traseal®

## SA-101

### 100% RTV ACETIC SILICONE SEALANT



#### 1. Product & Company Identification

##### Product Details

Product name: SA-101 100% RTV Acetic Silicone Sealant  
Physical form: Paste  
Odour: Vinegar Odour  
CAS No.: Mixture

##### Company Details

Manufacturer: Mohm Chemical Sdn Bhd  
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,  
81100 Johor Bahru, Johor, Malaysia.  
Tel: + 60-7-3331222  
Fax: + 60-7-3320545 / + 60-7-333791

#### 2. Hazards Identification

##### Hazard Pictogram



Signal Word: Warning

##### Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

##### Hazard Statement

H315 - Causes skin irritation.  
H319 - Causes serious eye irritation

##### Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

##### Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical advice/attention.

##### Precautionary Statement – Storage

No precautionary statement



# SAFETY DATA SHEET

REV: 03 DATE: 13 APRIL 2015

# x'traseal®

## SA-101

### 100% RTV ACETIC SILICONE SEALANT



#### Precautionary Statement – Disposal

No precautionary statement

### 3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Titanium dioxide	13463-67-7	< 5 %
Methyltriacetoxysilane	4253-34-3	< 5 %
Treated Fume Silica	68611-44-9	5 – 15 %

### 4. First-aid Measures

Take off all contaminated clothing immediately.  
In case of ingestion: Seek medical advice immediately.  
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.  
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

### 5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.  
Unsuitable extinguishing media: Unknown  
Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde.

### 6. Accidental release measures

Methods for cleaning up: Take up mechanically.

### 7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety shoes.  
Protection against fire/explosion: General rules of fire prevention should be observed.  
Storage: Keep container tightly closed and dry.  
Cautions: Extreme heavy in drum form if product packed in 200L drum.

### 8. Exposure control / Personal protection

Ingredients with limited values to be Not indicated.



# SAFETY DATA SHEET

REV: 03 DATE: 13 APRIL 2015

# x'traseal®

## SA-101



### 100% RTV ACETIC SILICONE SEALANT

controlled:	
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/protective glasses.
Flammability:	Combustible

#### 9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.01 ± 0.02
Colour:	Clear and pigmented
Viscosity:	Not indicated.
Odour:	Acetic vinegar.
Volatile, % volume (25°C):	< 10%
Solubility in water:	Insoluble
Boiling point:	Not Applicable
Flash point:	Not Applicable
Ignition temperature:	Not Applicable

Note: the above information is not intended for use in preparing specification.

#### 10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	Water
Conditions to be avoid:	High temperature.
Dangerous reactions:	None known.
Dangerous products of decomposition:	Carbon dioxide, carbon monoxide, silicone dioxide, acetic acid, formaldehyde.

#### 11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect, On the skin:	Irritant for skin and mucous membranes.
On the eye:	irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

#### 12. Ecological Information

Complete information not yet available.

#### 13. Disposal considerations



# SAFETY DATA SHEET

REV: 03 DATE: 13 APRIL 2015

# x'traseal®

## SA-101



### 100% RTV ACETIC SILICONE SEALANT

For cured sealant landfill may be suitable.  
With respect to local regulation, dispose of to suitable incineration plant.

#### 14. Transport Information

Proper shipping name:	Silicone Sealant
Hazard technical name:	Not available.
Hazard class:	Not available.

No dangerous goods under the transport regulation.

#### 15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

#### 16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

\*\*\* End Of SDS \*\*\*



**MOHM CHEMICAL SDN. BHD.** (REG NO 276851-U)  
No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor Darul Takzim, Malaysia.  
Tel : +607 333 1222 Fax : +607 332 0545 / 333 7919  
No.43, Jalan Tambur 33/19, Seksyen 33, Shah Alam Technology Park, 40400 Shah Alam, Selangor Darul Ehsan, Malaysia.  
Tel : +603 5124 0876 / 5124 0878 Fax : +603 5124 0877

Page 4 of 4

Mohm Chemical Sdn. Bhd. is an ISO 9001 certified company in Malaysia.  
x'traseal® is a registered trademark of Mohm Chemical Sdn. Bhd.  
©1993 Mohm Chemical Sdn. Bhd. All rights reserved.  
Website: [www.xtraseal.com](http://www.xtraseal.com) Email : [info@mochem.com](mailto:info@mochem.com)