

XHAUST GUM

EXHAUST REPAIR CEMENT



ISO 9001

1. Product & Company Identification

Product Detail

Product name: XHAUST GUM CEMENT

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2
Specific target organ toxicity-single exposure	Category 3

Hazard Statement

H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.

Precautionary Statement – Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.



XHAUST GUM

EXHAUST REPAIR CEMENT



ISO 9001

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 – Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statement – Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statement – Disposal

P501 - Dispose of contents/container in compliance with all local and national regulations.

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Sodium Silicate	1344-09-8	50-60
Water	7732-18-5	~3
Filler	Proprietary	~40

4. First-aid Measures

In case of ingestion:	If swallowed, seek medical advice immediately and show this container or label. DO NOT INDUCE VOMITING. If ingested, induce vomiting, but only under medical supervision. Seek medical attention.
In case of skin contact:	Remove contaminated clothing. Wash off immediately with plenty of soap and water. Seek medical attention if irritation or symptoms persist. Wash all contaminated clothing before reuse.
In case of eyes contact:	Rinse immediately with plenty of water for 15 minutes clothing holding the eyelids open. Seek medical attention if irritation or symptoms persist.
In case of inhalation:	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.

5. Fire Fighting Measures

Flash Point °F(C°):	None
Recommended Extinguishing Media:	Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures:	Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact.
Hazardous Products of Combustion:	None
Unusual Fire/Explosion Hazards:	None
Lower Explosive Limit:	Not determined.
Upper Explosive Limit:	Not determined.

6. Accidental release measures

Personal precautions:	Evacuate personnel to a safe area. Keep personnel away from spill. Surfaces contaminated with the product will become slippery.
Environmental precautions:	Do not allow product to enter drains. Do not flush into surface water. Prevent further spillage if safe.
Clean-up methods:	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labeled containers for disposal.



XHAUST GUM

EXHAUST REPAIR CEMENT



ISO 9001

7. Handling and Storage

Storage: Store in a cool, dry area.
Handling: Avoid contact with skin and eyes. Wash hands before eating and smoking.

8. Exposure control / Personal protection

Eyes: Safety glasses.
Skin: Neoprene, rubber or butyl rubber gloves.
Ventilation: Provide adequate ventilation .
Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. Physical and Chemical Properties

Form: Gray Viscous Paste
Colour: Gray
pH: 11-12
Odour: Slight
Flash Point: NA

10. Stability and Reactivity

Stability: Stable under normal conditions.
Incompatibility (material to be avoid): None known
Conditions to be avoid: None
Dangerous products of decomposition: None known

11. Toxicological Information

Acute toxicity: No information
Irritation Data: No information

12. Ecological Information

Ecotoxicity: No data is available on this product.
Mobility: No data is available on this product.
Degradability: No data is available on this product.
Bioaccumulation: No data is available on this product.
Further information: No data is available on this product.



XHAUST GUM

EXHAUST REPAIR CEMENT



ISO 9001

13. Disposal Considerations

General information:	Dispose of in compliance with all local and national regulations. Do not allow product to enter drains. Do not empty into drains.
Disposal methods:	Dispose of in compliance with all local and national regulations.
Disposal of packaging:	Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.

14. Transport Information

Further information: The product is not classified as dangerous for carriage.

15. Regulatory Information

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.
NONE

California Proposition 65 No California Prop 65 chemicals are known to be present.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***

