

WOOD FILLER



ISO 9001

1. Product & Company Identification

Product Details

Product name: Wood Filler
Physical form: Paste
Odour: Mild Vinyl Acetate Odour
CAS No.: Mixture
Flammability: Material may not burn in wet state

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2
May cause respiratory irritation	Category 3

Hazard Statement

H315 - Causes skin irritation.
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.



WOOD FILLER



ISO 9001

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P304 + P340 - IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statement – Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.

Precautionary Statement – Disposal

P501 - Dispose of contents/container in accordance with regulations made under the control of Pollution & Environmental Protection Acts.

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Limestone	1317-65-3	30 – 70 %
Vinyl Acetate Polymer	9003-20-7	1 – 10 %
Dibutyl Phthalate	84-74-2	1 – 10 %
Mineral Spirits	64742-48-9	1 – 5 %
Iron Oxide	1317-60-8	1 – 5 %

4. First-aid Measures

Take off all contaminated clothing immediately.
In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: Water, foam, CO2, dry power and all standard fire-fighting media.
Unsuitable extinguishing media: Unknown
Hazardous decomposition: Not specified.

6. Accidental release measures

Methods for cleaning up: Take up mechanically and washing thoroughly with water.

7. Handling and Storage

Protection against fire/ explosion: General rules of fire prevention should be observed.
Storage: Keep container tightly closed and dry.
Cautions: Extreme heavy in drum form if product packed in 200L drum.



WOOD FILLER



ISO 9001

8. Exposure control / Personal protection

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/ protective glasses.

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.65 ± 0.05
Colour:	Natural and Teak
Viscosity:	Not indicated.
Odour:	Mild Vinyl Acetate Odour
Volatile % (25°C):	< 20%
Solubility in water:	Yes
Boiling point:	100°C
Flash point:	Non known
Ignition temperature:	Non known

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	None known
Conditions to be avoid:	None known
Dangerous reactions:	None known.
Dangerous products of decomposition:	No dangerous decomposition products known.

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect,	
On the skin:	Irritant for skin and mucous membranes
On the eye:	irritant effect
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of it to suitable incineration plant.



WOOD FILLER



ISO 9001

14. Transport Information

Proper shipping name: Latex based Sealant
Hazard technical name: Not available.
Hazard class: Not available.
No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements of EC directives.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***

