

625° F BLACK

RTV GASKET MAKER (ACETOXY)



ISO 9001

1. Product & Company Identification

Product Details

Product name: 625°F Black RTV Gasket Maker (ACETOXY)
Physical form: Paste
Odour: Acetoxy odour
Colour: Black
CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545 / + 60-7-3337919

2. Hazards Identification

Hazard Pictogram



Signal Word: Warning

Classification

Skin corrosion or irritation	Category 2
Serious eye damage or eye irritation	Category 2

Hazard Statement

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

Precautionary Statement – Prevention

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



625° F BLACK

RTV GASKET MAKER (ACETOXY)



ISO 9001

P337 + P313 - If eye irritation persists: Get medical advice/attention.

Precautionary Statement – Storage

No precautionary statement.

Precautionary Statement – Disposal

No precautionary statement.

3. Composition / Hazardous Components

Chemical Name

	<u>CAS No.</u>	<u>WT%</u>
Titanium dioxide	13463-67-7	< 5%
Methyltriacetoxysilane	22984-54-9	< 10 %
Treated Fume Silica	68611-44-9	5 – 15 %

4. First-aid Measures

Take off all contaminated clothing immediately.

In case of ingestion: Seek medical advice immediately.
In case of skin contact: Wipe with paper towel and immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: All standard fire-fighting media.
Unsuitable extinguishing media: Unknown
Hazardous decomposition: Carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides, iodine compounds, sulphur oxides, metal oxides and formaldehyde.

6. Accidental release measures

Methods for cleaning up: Take up mechanically.

7. Handling and Storage

Handling: Avoid contact with eyes and skin. Ensure good ventilation during processing. Wear safety goggles, gloves and shoes.
Protection against fire /explosion: General rules of fire prevention should be observed.
Storage: Keep container tightly closed and dry, store away from oxidizing materials.



625° F BLACK

RTV GASKET MAKER (ACETOXY)



ISO 9001

8. Exposure control / Personal protection

Ingredients with limited values to be controlled:	Not indicated.
Local exhaust:	Recommended
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/ protective glasses.
Flammability:	Combustible

9. Physical and Chemical Properties

Form:	Paste
Specific gravity:	1.03 ± 0.01
Colour:	Black
Viscosity:	Not indicated.
Odour:	Acetic
%Volatile (25°C):	< 10%
Solubility in water:	Insoluble
Boiling point:	Not known
Flash point:	Not known
Ignition temperature:	Not known
Note: the above information is not intended for use in preparing specification.	

10. Stability and Reactivity

Chemical stability:	Stable
Incompatibility (material to be avoid):	Water
Conditions to be avoid:	High temperature
Materials to avoid:	Oxidizing material can cause a reaction.
Dangerous products of decomposition:	Acetic acid during curing.
In case of fire, carbon dioxide, carbon monoxide, silicone dioxide and nitrogen oxides, iodine compounds, sulphur oxides, metal oxides and formaldehyde.	

11. Toxicological Information

Acute toxicity:	Not determined
Primary irritant effect,	
On the skin:	Irritant for skin and mucous membranes.
On the eye:	Irritant effect
Sensitization:	Sensitization possible by inhalation.
Additional Toxicological information:	When used and handled according to specification, the product does not have any harmful effects according to our experience and the information provided to us.



625° F BLACK

RTV GASKET MAKER (ACETOXY)



ISO 9001

12. Ecological Information

Complete information not yet available.

13. Disposal considerations

For cured sealant landfill may be suitable.
With respect to local regulation, dispose of it to suitable incineration plant.

14. Transport Information

Proper shipping name: **Silicone Sealant**
Hazard technical name: **Not available.**
Hazard class: **Not available.**
No dangerous goods under the transport regulation.

15. Regulatory Information

Labeling (EC): This product is not subject to the labeling requirements.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***

