

SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL

SAE15W-40(API CF-4/SG)

1. Product & Company Identification

Product Details

Product name: XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL
SAE15W-40(API CF-4/SG)

Physical form: Liquid

Odour: Mild hydrocarbon

CAS No.: Mixture

Company Details

Manufacturer: Mohm Chemical Sdn Bhd

Address: No. 32, Jalan Temenggong, Off Jalan Tampoi,
81100 Johor Bahru, Johor, Malaysia.

Tel: + 60-7-3331222

Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram

-

Signal Word: -.

Classification

Not classified.

Hazard Statement

No precautionary statement

Precautionary Statement – Prevention

No precautionary statement

Precautionary Statement – Response

No precautionary statement

Precautionary Statement – Storage

No precautionary statement

Precautionary Statement – Disposal

No precautionary statement



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL

SAE15W-40(API CF-4/SG)

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>CAS No.</u>	<u>WT%</u>
Hydrogenated Base Oil	64742-54-7	25-50 %
Hydrogenated Base Oil	-	5-10 %

4. First-aid Measures

Eye Contact :	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Skin Contact :	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Inhalation :	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if symptoms occur.
Ingestion :	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

5. Fire Fighting Measures

Suitable extinguishing media :	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media :	None known.
Special firefighting procedure :	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazardous decomposition :	Carbon dioxide, carbon monoxide, smoke

6. Accidental release measures

Methods for cleaning up:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor
Environmental precautions:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL

SAE15W-40(API CF-4/SG)

7. Handling and Storage

Precautions for safe handling

Protective measures:

Put on appropriate personal protective equipment. Avoid contact with used product. Do not reuse container.

Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage including any incompatibilities:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure control / Personal protection

Control parameters

Occupational exposure limits:

Under conditions which may generate mists, the following exposure limits are recommended: ACGIH TLV TWA: 5 mg/m³ ; STEL: 10 mg/m³.

Appropriate engineering controls:

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls:

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Hand protection:

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection:

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL SAE15W-40(API CF-4/SG)

Respiratory protection: should be approved by a specialist before handling this product.
Not required under normal conditions of use.

9. Physical and Chemical Properties

Form:	Liquid
Colour:	Amber
Odour:	Mild hydrocarbon.
Density, kg/litre @15°C	0.870
Flashpoint COC, °C:	>220
Kinematic Viscosity ,mm ² /s @40°C	105.0
Kinematic Viscosity, mm ² /s @100°C	14.6
Pour Point, °C	-33

10. Stability and Reactivity

Reactivity:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability:	The product is stable.
Incompatibility (material to be avoid):	Oxidizing materials.
Conditions to be avoid:	Keep away from sources of ignition.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous decomposition products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

Acute toxicity

There is no data available.

Carcinogenicity

Product/ingredient name : Hydrogenated Base Oil (64742-54-7)

OSHA :-

IARC :-

NTP :-

ACGIH :A4

EPA :-

NIOSH :-

Irritation/Corrosion

There is no data available.



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL

SAE15W-40(API CF-4/SG)

Sensitization

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

Name : Hydrogenated Base Oil (64742-54-7)

Result : ASPIRATION HAZARD - Category 1

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Skin contact : No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

12. Ecological Information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

There is no data available.

Mobility in soil

Soil/water partition coefficient (K_{OC}) : There is no data available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal Considerations



SAFETY DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XD XTRA DYNAMIC PREMIUM MINERAL ENGINE OIL

SAE15W-40(API CF-4/SG)

Waste Disposal Method:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport Information

DOT shipping name : non-regulated
DOT label : not applicable
DOT identification No.: not applicable
Supplemental section 12 information:
IMDG, IATA/ICAO, TDG – non – regulated

15. Regulatory Information

U.S. Federal regulations:

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Zinc Alkyldithiophosphate

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***

