

BT-390

WINDSCREEN SEALANT

1. Product & Company Identification

Product Details

Product name: BT-390 Windscreen Sealant
 Physical form: Extruded solid putty tape
 Odour: Odourless
 CAS No.: Mixture
 Flammability: Very low

Company Details

Manufacturer: Mohm Chemical Sdn Bhd
 Address: No. 32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
 Tel: + 60-7-3331222
 Fax: + 60-7-3320545/ + 60-7-3337919

2. Hazards Identification

Hazard Pictogram

None.

Classification

None.

Hazard Statement

None.

This Product is not classified as hazardous under current regulations.

3. Composition / Hazardous Components

<u>Chemical Name</u>	<u>Hazardous</u>
Synthetic Rubber	Non currently known

4. First-aid Measures

In case of swallowed	If large amount is swallowed, get medical attention
In case of inhalation	If adverse effects occur, remove to uncontaminated area. Get good medical attention.
In case of skin contact:	Wash exposed skin with hand cleaner / soap & water. Cool with water for at least 15 minutes if hot material is used.
In case of eyes contact:	Flush eyes with plenty of clean running tap water for at least 15 minutes
Advice to doctor:	Treat symptomatically.

5. Fire Fighting Measures

Flammability:	Very Low
Suitable extinguishing media:	Dry Chemical, Foam, CO ² , Water Fog
Flash Point	Minimum 180 °C



BT-390

WINDSCREEN SEALANT

6. Accidental release measures

Methods: Exclude sources of ignition and ventilation the area
Exclude non-essential personnel. Avoid breathing vapour

7. Handling and Storage

Handling: Ensure good ventilation during processing. Wear safety shoes.
Protection against fire/ explosion: General rules of fire prevention should be observed.
Storage: Keep in a cool shaded place, away from heat & direct sunlight.

8. Exposure control / Personal protection

Hand protection: Suitable protective gloves.
Eye protection: Safety / Protective Goggles

9. Physical and Chemical Properties

Form: Extruded solid putty tape
Specify gravity: 1.4 ± 0.1
Colour: Black
Odour: Odourless
Melting Temperature Not Applicable
Boiling point: Not Applicable
Flash point: Minimum 180 °C
Freezing Point Not Applicable
Ignition Temperature: Non known
Vapour Pressure (25°C) Non known
Soluble in Water (25°C) Negligible, below 1%

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Hazardous Decomposition Products: Incomplete burning can produce CO, CO₂, and other harmful products.
Hazardous Reaction: No dangerous reaction known

11. Toxicological Information

On the skin: May cause sensitization
On the eye: Possibility irritating

12. Ecological Information

Large quantities of products should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface water.

13. Disposal considerations

Do not allow large quantities to enter the drains or watercourses or dispose of where ground surface may be affected. Residue in emptied containers should be covered and should be disposed of in accordance



BT-390

WINDSCREEN SEALANT

with regulations made under the control of Pollution & Environment Protection Acts.

14. Transport Information

Not Available

15. Regulatory Information

Not Available.

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of SDS ***

