

BT-390

WINDSCREEN SEALANT (BUTYL TAPE)

DESCRIPTION:

x'traseal® BT-390 WINDSCREEN SEALANT (BUTYL TAPE) IS A BLACK, NON-HARDENING SYNTHETIC RUBBER BASED. IT IS A STICKY RIBBON TYPE AUTO GLASS REPLACEMENT SEALER USED FOR THE INSTALLATION OF ALL GASKETS LESS WINDSHIELDS AND BACKLITES. BT-390 OFFERS A FAST AND CLEAN METHOD FOR INSTALLING THE GLASS. INSTANTLY WITH SUPERIOR ADHESION. THE SEALER HAS EXCELLENT COMPRESSIBILITY IN BOTH LOW / HIGH TEMPERATURES. IT IS DESIGNED TO MAINTAIN POSITION, PERMANENTLY SEALING AND WATERPROOFING BETWEEN THE GLASS AND PINCH WELD.

SPECIFICATION:

BASE	BUTYL RUBBER
APPEARANCE	BLACK
HARDNESS IRHD	25 ± 1
SPECIFIC GRAVITY	1.4 ± 0.10
HEAT RESISTANCE	100°C
WATER RESISTANCE	EXCELLENT
SERVICE TEMPERATURE	- 20°C to 70°C
ORDOR	NON OR VERY LITTLE
ADHESION	GOOD ON METAL, GLASS, WOOD AND CONCRETE
STORAGE	PRODUCT IS VERY INERT AND CAN LAST ALMOST INDEFINITELY WITHOUT DETERIORATING

APPLICATION:

- ◆ REMOVE THE WINDSHIELDS AND OLD SEALANT MATERIAL FROM SURFACES THOROUGHLY.
- ◆ SURFACE MUST BE CLEAN, DRY AND FREE FROM GREASE, OIL AND DIRT.
- ◆ HAND PRESSED THE TAPE INTO PLACE GROUND THE PINCH WELD. REPLACE NEW SETTING BLOCKS IF ORIGINAL BLOCKS ARE DAMAGED.
- ◆ PLACE THE WINDSCREEN OVER THE TAPE AND APPLY PRESSURE EVENLY TO ENSURE WATER TIGHT ACHIEVED.

TIPS:

- ◆ THIS TAPE CAN BE USED ALONE OR IN COMBINATION WITH OTHER SEALANTS, EG. POLYURETHANE OR SILICONE SEALANT DEPENDING UPON THE TYPE OF INSTALLATION.
- ◆ IN EXTREMELY COLD WEATHER CONDITIONS, IT IS RECOMMENDED TO WARM THE BUTYL TAPE FOR THE BETTER WORKABILITY.

CAUTION:

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

