

MC-202



ISO 9001

X' MASTIC NON-SKINNING COOLROOM SEALANT

DESCRIPTION:

x'traseal® x-mastic IS A ONE COMPONENT, NON-DRYING POLYBUTENE RUBBER BASED MASTIC THAT DOES NOT HARDEN BUT RATHER REMAINS PERMANENTLY SOFT AND PASTE-LIKE. EXCELLENT RESISTANCE TO WATER VAPOUR TRANSMISSION.

FEATURES:

- ◆ PERMANENTLY NON-SKINNING.
- ◆ LOW SHRINKAGE.
- ◆ MOISTURE RESISTANCE.
- ◆ EXCELLENT ADHESION.

USES:

IT'S SUITABLE FOR ALL KINDS OF PLASTICS, METALS, GLASS, MASONRY AND TIMBER. IT ALSO CAN BE USED IN THE INSTALLATION OF COOLROOMS AND PREFABRICATED CONSTRUCTION.

WE RECOMMEND PRELIMINARY COMPATIBILITY TESTS PRIOR TO APPLICATION TO ACHIEVE DESIRABLE RESULTS

NOT RECOMMENDED FOR:

IT SHOULD NOT BE APPLIED IN EXPOSED JOINTS WHERE DIRT PICK-UP AND HAND CONTACT. NOT FOR: USED IN AREAS SUBJECT TO CONSIDERATE DYNAMIC STRESS. NOT FOR: MOBILE HOMES, TRUCK BODIES.

COLOUR:

WHITE, ALMOND. OTHER COLOURS ARE AVAILABLE UPON REQUEST.

APPLICATION:

- ◆ SURFACE MUST BE CLEAN AND DRY.
- ◆ CUT NOZZLE TO DESIRED SIZE.
- ◆ INSERT CARTRIDGE INTO CAULKING GUN.
- ◆ PUSH SEALANT AHEAD FOR UNIFORM BEAD.
- ◆ CLEAN OFF EXCESS SEALANT WITH KEROSENE OR MINERAL SPIRITS.

SPECIFICATION :

FORM	NON-SAGGING PASTE.
COLOUR	WHITE
SPECIFIC GRAVITY	1.60 ± 0.05
SLUMP	2.5 MM MAXIMUM
SHRINKAGE	5 % MAXIMUM
SERVICE TEMP.	- 40° C TO 80° C

CAUTION:

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET OF THIS PRODUCT BEFORE HANDLING OR USING.

This information is provided in good faith and is believed accurate based on a review of current composition and information supplied by vendors. No warranty is expressed or implied. Liability is expressly disclaimed.

