

TECHNICAL DATA SHEET

REV: 00 DATE: 4 OCTOBER 2016

XR XTRA RACING SEMI SYNTHETIC

SAE10W-40(API CI-4/SL)

XR XTRA RACING SAE 10W-40 specifically formulated semi synthetic motor oil using carefully selected additives for the perfect balance between performance and value. Provides increased cleaning and protection properties, together with high thermal stability and also extends oil-drain intervals. Meets and exceeds API CI-4/SL standards. It features x'traseal exclusive "Low-SAPS" additive technology and a unique anti-wear system.

BENEFITS

- Combines high performance and value for all types of diesel & gasoline engines.
- Increases short and long term engine performance.
- Reduces engine deposits to help maximize engine response.
- Delivers high protection across a variety of engine speeds, conditions and temperatures.
- Sustains high performance even during severe diving conditions.

TYPICAL PROPERTIES

SEMI SYNTHETIC MOTOR OIL

Characteristic	Unit	ASTM Method	RESULT
Colour			2.0
Specific Gravity @ 15°C			0.846
Kinematic Viscosity @ 100°C	cSt	D445	14.1
Kinematic Viscosity @ 40°C	cSt	D445	94.56
Viscosity Index			152
Flash Point COC, °C	°C		210
Pour Point	°C	D97	-30

Caution: Do not fill container with fuel /solvent- static could cause fire. Avoid prolong and repeat skin contact with the used oils. Protect the environment by disposing of used oil properly.

